Drikette® Page 1 of 6



SAFETY DATA SHEET

EFFECTIVE DATE: May 29, 2015 **SDS NUMBER:** M23

SECTION 1 – PRODUCT AND COMPANY INFORMATION

Product Name: Drikette®

Product Use: Moisture Absorbent
Grades: Paper SG 145
Synonyms: Desiccant

Company: Multisorb Technologies **Address:** 325 Harlem Road

Buffalo, NY 14224-1893 USA

Telephone Number: (716) 824 8900 [USA] Monday - Friday (8:00 - 5:00 EDT)

Fax Number: (716) 824 4091 [USA] Website / E-Mail: www.multisorb.com

SECTION 2 – HAZARD IDENTIFICATION

Emergency Overview:

A thick heavy white paper material that that poses little or no immediate hazard. The dust may cause irritation but most of the ingredients are bound together. This material is partially combustible. The cellulose is combustible but the silica gel is not combustible. Not a hazardous substance or mixture according to the Global Harmonized System (GHS).

GHS classification of the substance or mixture: Not a hazardous substance or mixture

GHS label elements, including precautionary statements: Not a hazardous substance or mixture

Hazardous not otherwise classified (HNOC) or not covered by GHS: None

Potential Health Effects:

Eyes: Dust may cause eye discomfort and irritation seen as reddening and tearing.

Skin: The product dust may cause drying of the skin.

Ingestion: Ingestion is unlikely, however will pass through the body normally.

Inhalation: Slight irritation is possible but none is expected.

Medical Effects Generally Aggravated by Exposure: None

Chronic Effects/Carcinogenicity: May cause eye, skin and mucous membrane irritation and drying.

Drikette[®] Page 2 of 6

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT NAME	CAS NUMBER	% BY WEIGHT	EC#	ANNEX #
A solid paper material containing silica gel	-	100% for the combination	-	-
Synthetic amorphous precipitated silica gel (SiO2)	112926-00-8	50-75%	231-545-4	Not Listed
Cellulose pulp	65996-61-4	20-30 %	265-995-8	Not Listed
Hydroxyethyl starch	9005-27-0	1-10 %	618-410-9	Not listed
Aluminum sulfate	10043-01-3	1-5%	233-135-0	Not Listed
Melamine resin	9003-08-1	1-5%	618-354-5	Not Listed

While this product is not classified as hazardous under GHS regulations, this SDS contains valuable information critical to the safe handling and proper use of this product.

This SDS should be retained and available for employees and other users of this product.

SECTION 4 – FIRST AID MEASURES

The following does not apply to the Drikette® but applies if the Drikette® is cut open and the person is exposed to the contents

Eyes: Rinse eyes well with water while lifting the eye lids. If irritation persists, consult a physician.

Skin: Wash affected area with soap and water.

Ingestion: Ingestion is unlikely, however, could cause blockage if it occurs. Get medical attention.

Inhalation: Not applicable

Notes to Physician: Not applicable

SECTION 5 – FIRE FIGHTING MEASURES

Flammable Properties: Not flammable

Flash Point: Not applicable **Method:** Not applicable

Flammable Limits: Not flammable

Lower Flammability Limit: Not applicable
 Upper Flammability Limit: Not applicable

Auto-ignition Temperature: Not applicable

Hazardous Combustion Products: Not applicable

Extinguishing Media: Use extinguishing media that is appropriate for the surrounding fire.

Silica gel is not combustible but the cellulose is combustible.

Fire Fighting Instructions: The silica gel is not combustible; however the cellulose is combustible.

Unusual Fire and Explosion Hazards: None

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill: Sweep or vacuum up and place the spilled material in a waste disposal container.

Wash with soap and water after handling. Refer to Section 8 for personal protective equipment.

SECTION 7 – HANDLING AND STORAGE

Handling: Minimize contact between the worker and the material.

Practice good hygienic work practices.

Storage: Store in a cool, dry location. Keep in sealed containers away from moisture.

Silica gel will readily adsorb moisture.

Incompatibility: Water, fluorine, oxygen difluoride, chlorine trifluoride

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Not applicableRespiratory Protection: Not applicableSkin Protection: Not applicableEye Protection: Not applicable

EXPOSURE LIMITS					
COMPONENT NAME	OSHA PEL	ACGIH TLV	OTHER RECOMMENDED LIMITS		
A solid material containing silica gel	Not Applicable	Not Applicable	Not Applicable		

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	A solid material containing a bonded granular material	VAPOR DENSITY:	Not applicable
ODOR:	None	BOILING POINT:	Not applicable
PHYSICAL STATE:	Solid granule	MELTING POINT:	Not applicable
PH:	Not applicable	SOLUBILITY:	Insoluble in water
VAPOR PRESSURE:	Not applicable	SPECIFIC GRAVITY:	Not applicable
FLAMMABLE:	Not applicable	AUTO-IGNITION POINT:	Not applicable
FLASH POINT:	Not applicable	FLAMMABLE LIMITS:	Not applicable
ODOR THRESHOLD:	None	EVAPORATION RATE:	Not applicable
PARTITION COEFFICIENT N-OCTANOL / WATER:	Not applicable	DECOMPOSITION TEMPERATURE:	Not known
VISCOSITY:	Not applicable		

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Conditions to avoid: Moisture and high humidity environments will reduce the desiccating capacity.

Incompatibility: Water, fluorine, oxygen difluoride, chlorine trifluoride

Hazardous Decomposition Products: None Hazardous Polymerization: Will not occur

Reactivity: None

SECTION 11 – TOXICOLOGICAL INFORMATION

The following toxicological information refers to the contents of the solid material. In normal use, there is no exposure to the contents.

This product and its components are not listed on the IARC, NTP or OSHA Carcinogen lists.

IARC: Amorphous silica gel IARC - 3 (Unclassifiable as to Carcinogenicity in Humans)

Animal Toxicology: Tests for DOT Hazard classification

(Tests conducted on finely ground silica gel)

1 - hour LC50 (rat) > 2 mg / l

48 - hour oral LD50 (rat) est. > 31,600 mg / kg

48 - hour dermal LD50 (rabbit) est. > 2,000 mg / kg

Considered an ocular irritant

Cellulose pulp (related to cellulose)

Inhalation LC50 Rat:> 5,800 mg / m3 / 4H

Oral LD50 Rat:> 5. gm / kg

Dermal LD50 Rabbit:> 2. gm / kg

Hydroxyethyl starch

Oral LD50 Rat:> 50. gm / kg

Oral LD50 Mouse:> 12. gm / kg

Aluminum sulfate

Oral LD50 Mouse: 6207 mg / kg

Human Toxicology: Silica gel is a synthetic amorphous silica not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects. In the activated form, silica gel acts as a desiccant and can cause a drying irritation of the mucous membranes and skin in cases of severe exposure. Multisorb Technologies knows of no medical conditions that are abnormally aggravated by exposure to silica

gel.

SECTION 12 – ECOLOGICAL INFORMATION

Environmental: Not hazardous

Ecotoxicity: *Freshwater Algae Data 72 hour EC50 Selenastrum capricomutum: 440mg / L

* Freshwater Fish Species Data 96 hour LC50Brachydanio rerio: 5,000 mg / L (static)

* Water Flea Data 48 hour EC50 Ceriodaphnia: 7,600 mg / L

*Silica, amorphous

Aluminum sulfate LC50 (96 hour) goldfish: 100 mg / L

Persistence and degradability: Not available

Bioaccumulative potential: Not available

Mobility in soil: Not available

Other adverse effects: Not available

SECTION 13 – DISPOSAL INFORMATION

Disposal Information:

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Materials of a hazardous nature that contact the product during normal use may be retained on the product. The user of the product must identify the hazards associated with the retained material in order to assess the waste disposal options. Dispose according to federal, state, provincial and local regulations

SECTION 14 – TRANSPORTATION INFORMATION

U.S. Department of Transportation Shipping Name: Not classified as a hazardous material. Not regulated. Non dangerous per IATA-DG regulations.

SECTION 15 - REGULATORY INFORMATION (NOT MEANT TO BE ALL INCLUSIVE - SELECTED REGULATIONS REPRESENTED)

The following regulatory information refers to the contents of the solid material. In normal use, there is no exposure to the contents.

TSCA Listed: Yes

OSHA: See section 8

NIOSH: See section 8

Animal tests conducted in 1976 - 1978. 18 month exposure at 15 mg/m³ showed silica

deposition in respiratory macrophages and lymph nodes, minimum lung impairment, no silicosis.

ACGIH: See section 8

DOT: Not classified as a hazardous material.

HMIS – HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HMIS RATING		
Health:	1	
Flammability:	0	
Physical:	0	

The HMIS rating information is intended solely for the use of individuals trained in the HMIS rating system.

The NPCA specifically recommends that preparers of SDS should not place HMIS PPE designation codes on the SDS or labels that leave the facility as it is not known the conditions under which the customer will use this product.

Date of Preparation: May 29, 2015

This data and recommendations presented in this data sheet concerning the use of our product and the materials contained therein are believed to be correct but does not purport to be all inclusive and shall be used only as a guide. However, the customer should determine the suitability of such materials for his purpose before adopting them on a commercial scale. Since the use of our products is beyond our control, no guarantee, expressed or implied is made, and no responsibility assumed for the use of this material or the results to be obtained there from. Information on this form is furnished for the purpose of compliance with Government Health and Safety Regulations and shall not be used for any other purposes. Moreover, the recommendations contained in this data sheet are not to be construed as a license to operate under, or a recommendation to infringe any existing patents, nor should they be confused with state, municipal or insurance requirements, or with national safety codes.