



E-FLARE™ BEACON COMPARISON

HOW DOES E-FLARE™ COMPARE WITH OTHER WARNING BEACONS CURRENTLY ON THE MARKET?



	E-FLARE™	ELITE™	TURBOFLARE™	VISIFLARE™	POWERFLARE™
BATTERY TYPE	4 x AA Cell	2 x D Cell	4 x D Cell	2 x D Cell	Lithium CR123
BATTERY LIFE	20+ hours	Up to 120 hrs on Consumer Model	88 hours	16 hours	100 hours
VISIBILITY	3/4 mile	1/6 mile in favorable conditions	Approx 5 miles	2 miles	1/2 mile
BRIGHTNESS (CANDELA)	Between 10 and 40 Candela depending on model	Between 0.5 and 2 Candela depending on battery condition	18 - 30 at any given moment 9 - 15 per LED	30	3.4 - 15.7 depending on mode
WATERPROOF	To 100 feet	N/A	Weatherproof	To 300 feet	To 80 feet
FLASH RATE (FPM)	165 - 185 flash/min	Fast (400/min) Slow (200/min) Steady burn	90 flash/min	60-75 flash/min	50-120 flash/min dependant on flash pattern
COLORS AVAILABLE	Red, Amber, Blue, Green or White. Five dual flash color combinations	Red or Amber	Amber or Red	Various	Red, Amber, Blue, Green & White
LIGHT SOURCE	LED's	LED's	LED's	Xenon "U" tube	LED's
MOUNTING	Rubber Base, Cone Clip, Magnetic Clip, Magnetic Base or Clip on the Body of Unit	Rubber base	Unit does not require a base as it lies flat on the ground	Roadside, Suction or Spike Base	Unit does not require a base as it lies flat on the ground

The information above was provided by Eflare Corporation Pty Ltd

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | sales@pipusa.com | www.pipusa.com