
DuPont[™] ProClean[®] Sleeves — Series 500

GARMENT TECHNICAL DATA SHEET



*Processing and Packaging Options (OB or OO = Bulk)

Option	OB or OO		
Processing			
Sterilization			
Packaging Conditions			
Packaging Configurations	Bulk packaged in double transparent poly liners		

This information is based upon technical data that DuPont believes reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under the specific end-use conditions, at their own discretion and risk.

Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures may provide less barrier than the fabric. If the fabric becomes torn, abraded or punctured, end user should discontinue use of garment to avoid compromising the barrier protection. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, NO WARRANTIES, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION. This information is not intended as a license to operate under or a recommendation to infringe any patent, trademark or technical information of DuPont or others covering any material or its use. WARNINGS: 1) DuPont garments and accessories for controlled environments are not flame-resistant and should not be used around heat, flame, sparks or in potentially flammable or explosive environments. 2)Garments made of Tyvek® should have slip-resistant or antislip materials on the outer surface of boots, shoe covers or other garment surfaces in conditions where slipping could occur. Fabric: Microporous composite fabric Attributes: Serged seams, covered elastic wrist and bicep, white

Product Information

Garment Data

Fabric Type	Series Type	Seam Type	Color	Sizes	Case Quantity	Options*
Catalog Number: PC500SWH000200‡‡				(When ordering replace ‡‡ with desired option.)		
PC (ProClean®)	500	S (Serged)	WH (White)	00 Universal	200 (each)	OB (See below for Processing and Packaging Options)

Typical Finished Dimensions

Size	Wrist Opening	Bicep Opening	Length
Universal	5 1/4"	7 3/4"	18 1/2"

Latex Statement—As of January 1, 2006 DuPont production specifications exclude use of components containing natural rubber latex in the manufacture of DuPont[™] ProClean[®] garments. Anyone who begins to exhibit allergic response during the use of DuPont products should immediately cease using these products. The incident should also be reported to DuPont at 1-800-441-3637.

Customer Service:

United States 1-800-931-3456 Canada 1-800-387-9326 Mexico 01800 849 75 14 or 011 52 55 5722 1150

www.ControlledEnvironments.DuPont.com



