

# DuPont™ Tyvek® Micro-Clean® 2-1-2 individually packaged garments

## TECHNICAL DATA SHEET

Protection and comfort in critical environments.



Tyvek® Micro-Clean® 2-1-2 apparel is breathable,  
lightweight and durable.

DuPont™ Tyvek® delivers a good balance of protection, durability and comfort. Made using a patented flash spinning process, Tyvek® features an inherent barrier. Every Tyvek® Micro-Clean® 2-1-2 garment is new, clean and fresh. Both inventory and use costs are predictable, allowing you to predict your costs without replacement, repair or restocking fees.

### Key Benefits

- Balance of protection, comfort and durability
- Excellent inherent barrier to dry particles and microorganisms
- Coated on both sides with proprietary 2-1-2 blue polymeric resin
- Cloth-like aesthetics
- Antistatic treated to reduce nuisance static
- Recyclable
- Available packaged individually and sterile
- High quality

For higher level of protection, inquire about Tyvek® IsoClean® garments that are clean processed and gamma irradiated to Sterility Assurance Level (SAL) of  $10^{-6}$ .

### Wide Range of Applications

Garments made of Tyvek® Micro-Clean® 2-1-2 are used in the biotech, pharmaceutical, medical device manufacturing and electronics industries, as well as in other critical or controlled environments. With a wide range of proven, science-based solutions, DuPont products help ensure superior protection for your business critical systems, equipment and controlled environment production processes.



*The miracles of science™*


## Typical Physical Properties of DuPont™ Tyvek® Micro-Clean® 2-1-2

Property	Units	Tyvek® Micro-Clean® 2-1-2	Standard
Basis Weight	oz/yd <sup>2</sup>	1.3	ASTM D3776
Thickness	mils	4.4	ASTM D1777
Bacterial Filtration Efficiency (3.0 μ)	%	98.9	ASTM F2101
Grab Tensile, MD	lbf	22.9	ASTM D5034
Grab Tensile, CD	lbf	20.2	ASTM D5034
Hydrostatic Head	cm H <sub>2</sub> O	48.0	AATCC TM127
Surface Resistivity (55% RH)	ohms	10 <sup>10</sup>	ASTM D257
Flammability		Class 1	16 CFR 1610


These properties are typical for garments that have not been clean-processed or sterilized. Sterilization may affect strength, water barrier and static dissipation.

### Seam Construction

Even the best protective fabrics are useless without strong, tight seams. Seam construction available in bound seams with covered elastic options.



**Bound**  
Tightly sewn with a reinforced outer binding to increase seam strength and barrier.



**Covered Elastic**  
Elastic covered by garment material so elastic is not exposed.

*This information is based upon technical data that DuPont believes reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under the specific end-use conditions, at their own discretion and risk.*

*Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures may provide less barrier than the fabric. If the fabric becomes torn, abraded or punctured, end user should discontinue use of garment to avoid compromising the barrier protection. **SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.** This information is not intended as a license to operate under or a recommendation to infringe any patent, trademark or technical information of DuPont or others covering any material or its use. **WARNINGS:** 1) DuPont garments and accessories for controlled environments are not flame-resistant and should not be used around heat, flame, sparks or in potentially flammable or explosive environments. 2) Garments made of Tyvek® should have slip-resistant or antislip materials on the outer surface of boots, shoe covers or other garment surfaces in conditions where slipping could occur.*

Copyright © 2009 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, Tyvek®, IsoClean® and Micro-Clean® 2-1-2 are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-22227 (07/09) Printed in the U.S.A.

#### Customer Service:

United States 1-800-931-3456  
Canada 1-800-387-9326  
Mexico 01800 849 75 14 or  
011 52 55 5722 1150

[www.ControlledEnvironments.DuPont.com](http://www.ControlledEnvironments.DuPont.com)



*The miracles of science™*