


#378GKGVB

# Endura®

Oilbloc™ Goatskin Kevlar®-Lined  
Anti-Impact Driver Gloves



Fully Kevlar® lined



#378GKGVB

Goatskin has high tensile strength and abrasion-resistant properties and is often referred to as nature's strongest leather. With smart styling and design, this drivers-style, goat-grain leather glove is fully lined with a blend of Kevlar® and composite filament fiber, offering ASTM cut-level 4 protection. The brown goatskin hides dirt and is also treated with Oilbloc™. The back of hand and fingers feature impact protection that's comfortably flexible and supremely durable. Inside palms are full goatskin leather with ultra-comfortable gel padding. Our cut-and-sewn liner dons much more easily than a seamless knit, thanks to the fine tailoring.

Because of a high strength-to-weight ratio, our Endura® goatskin all-leather drivers are much tougher and more durable than their suppleness leads you to think.

Arc-flash testing placed these gloves at level 3, with a rating of ATPV = 36 Cal/cm². Note: these gloves are designed for spark and flame resistance, not thermal contact.

For more information on Cut-Resistant Anti-Impact Gloves click the following link:

<http://www.superiorglove.com/work-gloves/impact-resistant-gloves/cut-resistant-anti-impact-gloves>

Kevlar® is a registered trademark of E.I. du Pont de Nemours and Company.

## Endura®

Canadian Office and Factory | US Warehouse  
Acton, ON Canada | Buffalo, NY USA  
1-800-265-7617 | [customerservice@superiorglove.com](mailto:customerservice@superiorglove.com)

European Office  
+44 (0) 7748 801 833 | [graham.ayers@superiorglove.com](mailto:graham.ayers@superiorglove.com)  
[superiorglove.com](http://superiorglove.com)



## 2500 grams of cut protection.

### FEATURES

- Padded palm for vibration dampening
- TPR anti-impact backing
- Kevlar® and composite filament fiber lining, ASTM Cut-Level 4 protection
- High tensile-strength goatskin provides outstanding abrasion resistance
- Water and oil repellent
- Level 3 arc-flash resistant according to ASTM F2675 / F2675M

### APPLICATIONS

Metal Handling  
Construction  
Steel Plants  
Oil and Gas  
Extrication

### AVAILABLE SIZES

