



887 Kensington Ave. Buffalo, NY 14215

<u>Pad Construction</u>	<u>Description</u>		
Construction			
Substrate 1	55 gsm Airlaid		
Absorbent	SAP		
Substrate 2	14# Single Ply Tissue		

<u>Description</u>	<u>STANDARD DATA</u>	<u>METRIC DATA</u>
Basis WT:	14.2 g/sq.ft.	153 g/sq.m
SAP WT:	7.4 g/sq.ft	80 g/sq.m
Thickness	25.0 Mils	635 microns
ABSORBENCY IN 0.9% NaCl		
30 SEC:	185 g/sq.ft.	1990 g/sq.m
5 MIN:	395 g/sq.ft	4250 g/sq.m
	27.8 g/g	27.8 g/g
ABSORBENCY IN DI water		
30 SEC:	407 g/sq.ft.	4381 g/sq.m.
5 MIN:	1741 g/sq.ft.	18740 g/sq.m.
	122.6 g/g	122.6 g/g
MD Tensile:	2.0 lb/in	0.9 kg/in
MD Elongation:	9.0 %	9.0 %
Yield:	4.1 sq.yd/lb	7.5 sq.m/kg

DATE: 38/06-38

NOTE: THIS TYPICAL DATA IS ONLY AN APPROXIMATION OF THE TRUE VALUES AND IS NOT TO BE USED FOR SPECIFICATION PURPOSES.